


## Adaptor Flange ANSI Standard



- Certificate: FM Approved / UL Listed
- Size: 2" - 24" (DN 50 - DN 600)
- Pressure: CLASS 125 / 150
- Dimensions: ANSI B16.3
- Material: ASTM A536, GRADE 65-45-12, QT450-10
- Threaded: ASME B1.20.1, ISO 7-1, GB 7306
- Surface: P: Painted E: Electroplated B: Black S: Epoxy G: Hot-dip Galvanized



### Available size

| SIZE   |       | OD SIZE | L (MM) | X (MM) | Y (MM) | Z (MM) |
|--------|-------|---------|--------|--------|--------|--------|
| 2"     | DN50  | 60.3    | 65     | 152    | 120.5  | 16     |
| 2 1/2" | DN65  | 73.0    | 65     | 185    | 139.7  | 16     |
| 3"     | DN80  | 88.9    | 65     | 200    | 152.4  | 16     |
| 4"     | DN100 | 114.3   | 70     | 229    | 190.5  | 16     |
| 6"     | DN150 | 168.3   | 70     | 282    | 241.3  | 18     |
| 8"     | DN200 | 219.1   | 75     | 340    | 298.5  | 19     |
| 10"    | DN250 | 273.0   | 85     | 406    | 362    | 21     |
| 14"    | DN350 | 355.6   | 127    | 535    | 476.3  | 37     |
| 16"    | DN400 | 406.4   | 127    | 595    | 539.8  | 37     |
| 18"    | DN450 | 457.2   | 140    | 642    | 577.8  | 40     |
| 20"    | DN500 | 508.0   | 152    | 700    | 635    | 43     |
| 24"    | DN600 | 609.6   | 152    | 815    | 749.3  | 49     |