


Forged BW Outlet (Weldolet)



- Certificate: ISO
- Standard: MSS SP-97
- Material : Carbon steel ASTM A 105 / Stainless steel
- Thickness: STD, XS, Sch160, XXS, etc.
- W. pressure: Equal to same seamless pipe
- Surface: Original / hot dip galvanized



Available size

Branch size		Run pipe size		Length A			OD of Fitting D2 min			Cut Hole Dia. d1		
NPS	DN	NPS	DN	STD	XS	Sch160	STD	XS	Sch160	STD	XS	Sch160
1/8"	6	1/4"-36"	8-900	16	16	-	24	24	-	16	16	-
1/4"	8	3/8"-36"	10-900	16	16	-	26	26	-	16	16	-
3/8"	10	1/2"-36"	15-900	19	19	-	30	30	-	19	19	-
1/2"	15	3/4"-36"	20-900	19	19	28	36	36	36	24	24	14
3/4"	20	1"-36"	25-900	22	22	32	43	43	46	30	30	19
1"	25	1-1/4"-36"	32-900	27	27	38	55	55	51	36	36	25
1-1/4"	32	1-1/2"-36"	40-900	32	32	44	66	66	63	45	45	33
1-1/2"	40	2"-36"	50-900	33	33	51	74	74	71	51	51	38
2"	50	2-1/2"-36"	65-900	38	38	55	90	90	82	65	65	43
2-1/2"	65	3"-36"	80-900	41	41	62	104	104	98	76	76	54
3"	80	3-1/2"-36"	90-900	44	44	73	124	124	122	93	93	73
4"	100	5"-36"	125-900	51	51	84	154	154	154	120	120	98
5"	125	6"-36"	150-900	57	57	94	187	187	188	141	141	122
6"	150	8"-36"	200-900	60	78	105	213	227	222	170	170	146
8"	200	10"-36"	250-900	70	99	-	265	292	-	220	220	-
10"	250	12"-36"	300-900	78	94	-	323	325	-	275	265	-
12"	300	14"-36"	350-900	86	103	-	379	381	-	325	317	-
14"	350	16"-36"	400-900	89	100	-	411	416	-	357	351	-
16"	400	18"-36"	450-900	94	106	-	465	468	-	408	403	-
18"	450	20"-36"	500-900	97	111	-	522	525	-	459	455	-
20"	500	22"-36"	550-900	102	119	-	573	584	-	508	509	-
24"	600	26"-36"	650-900	116	140	-	690	708	-	614	612	-