


Grooved 90° Reducing Elbow With Threaded Outlet



- Certificate: FM Approved / UL Listed
- Size: 1 1/4"×1/2" - 3"×1" (DN 32×15 - DN 80×25)
- Pressure: 500PSI
- Dimensions: ANSI B16.3
- Material: ASTM A536, GRADE 65-45-12, QT450-10
- Threaded: ASME B1.20.1, ISO 7-1, GB 7306
- Surface: P: Painted E: Electroplated B: Black S: Epoxy G: Hot-dip Galvanized



Available size

SIZE		OD SIZE	L 1(MM)	L 2(MM)
1 1/4"×1/2"	DN32×DN15	42.4X21.3	35.1	44.5
1 1/4"×3/4"	DN32×DN20	42.4X26.9	34.9	47.6
1 1/4"×1"	DN32×DN25	42.4X33.7	38.1	51.6
1 1/2"×1/2"	DN40×DN15	48.3X21.3	34.9	44.5
1 1/2"×3/4"	DN40×DN20	48.3X26.9	34.9	47.6
1 1/2"×1"	DN40×DN25	48.3X33.7	38.1	51.6
2"×1/2"	DN50×DN15	60.3X21.3	41.4	44.5
2"×3/4"	DN50×DN20	60.3X26.9	41.3	47.6
2"×1"	DN50×DN25	60.3X33.7	44.5	51.6
2 1/2"×1/2"	DN65×DN15	73.0X21.3	46	44.5
2 1/2"×3/4"	DN65×DN20	73.0X26.9	46	47.6
2 1/2"×1"	DN65×DN25	73.0X33.7	49.2	51.6
2 1/2"×1"	DN65×DN25	76.1X33.7	49.2	51.6
3"×3/4"	DN80×DN20	88.9X26.9	60.3	52.4
3"×1"	DN80×DN25	88.9X33.7	63.5	52.4