



Grooved Cap With Eccentric Hole



- Certificate: FM Approved / UL Listed
- Size: 2 1/2"×1" - 12"×1 1/2" (DN 65×25 - DN 300×40)
- Pressure: 500PSI
- Dimensions: ANSI B16.3
- Material: ASTM A536, GRADE 65-45-12, QT450-10
- Threaded: ASME B1.20.1, ISO 7-1, GB 7306
- Surface: P: Painted E: Electroplated B: Black S: Epoxy G: Hot-dip Galvanized



Available size

SIZE		OD SIZE	L (MM)
2 1/2"×1"	DN65×DN25	76.1X33.7	23.5
2 1/2"×1 1/2"	DN65×DN40	76.1X48.3	23.5
3"×1"	DN80×DN25	88.9X33.7	23.5
3"×1 1/2"	DN80×DN40	88.9X48.3	23.5
3"×2"	DN80×DN50	88.9X60.3	23.5
4"×1"	DN100×DN25	114.3X33.7	27
4"×1 1/2"	DN100×DN40	114.3X48.3	25.4
4"×2"	DN100×DN50	114.3X60.3	25.4
5"×1"	DN125×DN25	139.7X33.7	27.3
5"×1 1/2"	DN125×DN40	139.7X48.3	25.4
5"×2"	DN125×DN50	139.7X60.3	25.4
6"×1 1/2"	DN150×DN40	165.1X48.3	25.4
6"×1 1/2"	DN150×DN40	168.3X48.3	25.4
6"×2"	DN150×DN50	168.3X60.3	25.4
8"×1 1/2"	DN200×DN40	219.1X48.3	30.2
8"×2"	DN200×DN50	219.1X60.3	30.2
10"×1 1/2"	DN250×DN40	273.0X48.3	33.1
12"×1 1/2"	DN300×DN40	323.9X48.3	31.2