


Grooved x Male Threaded



- Certificate: FM Approved / UL Listed
- Size: 2"×1" - 4"×3" (DN 50×25 - DN 100×80)
- Pressure: 300PSI
- Dimensions: ANSI B16.3
- Material: ASTM A536, GRADE 65-45-12, QT450-10
- Threaded: ASME B1.20.1, ISO 7-1, GB 7306
- Surface: P: Painted E: Electroplated B: Black S: Epoxy G: Hot-dip Galvanized



Available size

SIZE		OD SIZE	L (MM)
2"×1"	DN50×DN25	60.3X33.7	64
2"×1 1/4"	DN50×DN32	60.3X42.4	64
2"×1 1/2"	DN50×DN40	60.3X48.3	64
2 1/2"×1"	DN65×DN25	73.0X33.7	64
2 1/2"×1 1/4"	DN65×DN32	73.0X42.4	64
2 1/2"×1 1/2"	DN65×DN40	73.0X48.3	64
2 1/2"×2"	DN65×DN50	73.0X60.3	64
2 1/2"×2"	DN65×DN50	76.1X60.3	64
3"×1"	DN80×DN25	88.9X33.7	64
3"×1 1/2"	DN80×DN40	88.9X48.3	64
3"×2"	DN80×DN50	88.9X60.3	64
3"×2 1/2"	DN80×DN65	88.9X73.0	64
4"×1"	DN100×DN25	114.3X33.7	76.1
4"×1 1/2"	DN100×DN40	114.3X48.3	76.1
4"×2"	DN100×DN50	114.3X60.3	76.1
4"×2 1/2"	DN100×DN65	114.3X73.0	76.1
4"×3"	DN100×DN80	114.3X88.9	76.1