


Malleable iron Reducing Tee (131R)



- Certificate: FM Approved / UL Listed / BSI / LPCB / NSF 61
- Size: DN20×15×15 - DN80×65×65
- Pressure: 2.5 Mpa / PN25
- Dimensions: BS EN10242
- Material: Malleable iron BS EN1562
- Threaded: BSPP (ISO228) / BSPT (ISO7-1)
- Surface: Black / Electrical galvanized / Hot-dip galvanized



Available size

SIZE		A (MM)	B (MM)	PCS/CTN.
3/4"×1/2"×1/2"	20×15×15	29	27	120
1"×1/2"×3/4"	25×15×20	31	29	120
1"×3/4"×3/4"	25×20×20	34	32	120
1-1/4"×1/2"×1"	32×15×25	33	31	80
1-1/4"×3/4"×1"	32×20×25	36	34	60
1-1/4"×1"×1"	32×25×25	39	36	60
1-1/4"×1-1/4"×1"	32×32×25	44.5	41	40
1-1/2"×1/2"×1-1/4"	40×15×32	35	34	32
1-1/2"×3/4"×1-1/4"	40×20×32	37	36	36
1-1/2"×1"×1"	40×25×25	40	36	28
1-1/2"×1"×1-1/4"	40×25×32	41	40	20
1-1/2"×1-1/4"×1"	40×32×25	45	41	16
1-1/2"×1-1/4"×1-1/4"	40×32×32	45	44.5	12
1-1/2"×1-1/2"×1"	40×40×25	48.5	45	16
1-1/2"×2"×1-1/4"	40×50×32	54	53	10
2"×1/2"×1-1/2"	50×15×40	37	35	10
2"×3/4"×1-1/2"	50×20×40	40	37	6
2"×1"×1-1/4"	50×25×32	43	40	64
2"×1"×1-1/2"	50×25×40	42	40	68
2"×1-1/4"×1-1/4"	50×32×32	47	44.5	60
2"×1-1/4"×1-1/2"	50×32×40	47	45	40
2"×1-1/2"×1"	50×40×25	51	45	42
2"×1-1/2"×1-1/2"	50×40×40	51	48.5	40
2"×2"×1"	50×50×25	57	51	40
2-1/2"×1/2"×2"	65×15×50	40.5	37	36
2-1/2"×3/4"×2"	65×20×50	43.5	40	30
2-1/2"×1"×2"	65×25×50	45	42	24
2-1/2"×1-1/4"×1-1/2"	65×32×40	51.5	45	30
2-1/2"×1-1/4"×2"	65×32×50	51.5	47	30

2-1/2"×1-1/2"×2"	65×40×50	54.5	51	36
2-1/2"×2"×2"	65×50×50	59.5	57	36
3"×1"×2-1/2"	80×25×65	49.5	47.5	36
3"×1-1/4"×2-1/2"	80×32×65	54.5	51.5	24
3"×1-1/2"×2-1/2"	80×40×65	57.5	54.5	24
3"×2"×2-1/2"	80×50×65	61.5	59.5	16
3"×2-1/2"×2-1/2"	80×65×65	71.5	68.5	16