


U-Bolt With Threaded Branch



- Certificate: FM Approved / UL Listed
- Size: 1"×1/2" - 3"×1" (DN 25×15 - DN 80×25)
- Pressure: 300 psi
- Dimensions: ANSI B16.3
- Material: ASTM A536, GRADE 65-45-12, QT450-10
- Threaded: ASME B1.20.1, ISO 7-1, GB 7306
- Surface: P: Painted E: Electroplated B: Black S: Epoxy G: Hot-dip Galvanized

Available size



SIZE		OD SIZE	A(MM)	B (MM)	H (MM)
1"×1/2"	DN25×DN15	33.7X21.3	89	58	45
1 1/4"×1/2"	DN32×DN15	42.4X21.3	89	58	49
1 1/4"×3/4"	DN32×DN20	42.4X26.9	89	58	49
1 1/4"×1"	DN32×DN25	42.4X33.7	89	58	49
1 1/2"×1/2"	DN40×DN15	48.3X21.3	89	58	52
1 1/2"×3/4"	DN40×DN20	48.3X26.9	89	58	52
1 1/2"×1"	DN40×DN25	48.3X33.7	89	58	52
2"×1/2"	DN50×DN15	60.3X21.3	89	58	58
2"×3/4"	DN50×DN20	60.3X26.9	89	58	58
2"×1"	DN50×DN25	60.3X33.7	89	58	58
2"×1 1/4"	DN50×DN32	60.3X42.4	89	58	58
2 1/2"×1/2"	DN65×DN15	73.0X21.3	109	58	68
2 1/2"×3/4"	DN65×DN20	73.0X26.9	109	58	68
2 1/2"×1/2"	DN65×DN15	76.1X21.3	109	58	68
2 1/2"×3/4"	DN65×DN20	76.1X26.9	109	58	68
2 1/2"×1"	DN65×DN25	76.1X33.7	109	58	68
3"×1"	DN80×DN25	88.9X33.7	146	74	80